

## OPTIONS & ACCESSORIES

The XRT1550 is the industry's toughest vehicle, and with hundreds of accessories to choose from, the most versatile, too. Don't see what you need here? Ask your dealer for a complete list.



Windshield & Canopy



FOPS (Falling Object Protection Structure)



Front Skid Plate



Nerf Bars



Brush Guard



Skid Plate



Tool Box



Electric Bed Lift



Winch



Bench Seats




Bed Mat




IntelliTach™  
62 in (157 cm) Plow Blade

## AVAILABLE COLORS



Red (Standard)



Green (Standard)



Realtree® HD™ Camo  
(Optional)



©2012 Club Car LLC. Club Car believes the information and specifications in this piece of literature were correct at the time of printing. Specifications, standard features, options, fabrics and colors are subject to change without notice. Some features may be unavailable when your vehicle is built. Some vehicles are pictured with options that may be available at extra cost or may not be available on some models. Ask your dealer about the availability of options and verify that the vehicle you ordered includes the equipment you ordered. There are no warranties, expressed or implied, contained herein. See the Limited Warranty in the owner's manual or write to: Club Car, PO Box 204658, Augusta, GA 30917. The company reserves the right to make design changes without obligation to make these changes on previously sold units or systems.

CCN 18040017 Rev 08/12

1.800.CLUBCAR WWW.CLUBCAR.COM

Club Car®

FIND YOUR

LIGHT-DUTY MEDIUM-DUTY HEAVY-DUTY

XRT1550 4X4

## LOOKING FOR A UTILITY VEHICLE THAT OUTPERFORMS IN RUGGED TERRAIN?

**TEST DRIVE ONE OF OUR XRT1550 SERIES VEHICLES.** The hardest jobs. The heaviest loads. The toughest conditions. Bring 'em on. Any of our Club Car's XRT1550 4x4s deliver best-in-class performance, comfort, durability and ease of maintenance, thanks to these new features:

**NEW 4-LINK SEMI-INDEPENDENT REAR SUSPENSION FOR INDEPENDENT PERFORMANCE WITH SOLID AXLE STRENGTH.** The world-standard for off-road vehicles like Jeeps and Land Rovers, the system is unique to Club Car in the U.S. UTV market. It offers:

- **A smoother ride and better ground clearance**, even when fully loaded. The vehicle can carry up to 1050 lb (476 kg) of cargo over rocky terrain and maintain its 8 in (21 cm) ground clearance while delivering a smooth, comfortable ride.
- **Vastly improved axle articulation**, or the ability to adapt to uneven terrain while maintaining ground contact on all four tires while preserving traction and torque.
- **Less wear and tear, improved durability and more nimble performance.**

Other improvements include a brake rotor upgrade that lets you replace the brake rotor without replacing the hub, a rear differential upgrade that improves wear life, and a new clutch design that optimizes performance and delivers longer, quieter service.

With the XRT1550, farmers, hunters, home owners with land, equestrians, small business owners and others can get out ... and stay out.



facebook YouTube

IR Ingersoll Rand



## DESIGNED TO OUTPERFORM!

- Rustproof aircraft-grade aluminum frame, impact-resistant front body with molded-in color, steel-sided cargo box and tube bumper for long life and good resale value.
- Exclusive IntelliTrak™ drive system, our automatic, full-time 4-wheel drive system.
- Choose a Kawasaki 20.1 hp (15 kW), 675 cc air-cooled gas or a Kubota 20 hp (15 kW), 719 cc, liquid-cooled diesel engine; two- or four-passenger model; or the XRT1550 IntelliTrak™ with hydraulic attachment system. The system accommodates three easy-to-install attachments, so it can do the job of four vehicles at a fraction of the time and costs.
- A 4-link semi-independent rear suspension system for a smoother ride and better ground clearance, even when fully loaded. The vehicle can carry up to 1050 lb (476 kg) of cargo over rocky terrain and maintain its ground clearance while delivering a smooth, comfortable ride.
- 800 -1050 lb (363 - 476 kg) bed capacity with slam-latch tailgate.
- Safety features like 4-wheel hydraulic disc brakes, four-point certified roll over protection system (ROPS), retractable seat belts and halogen headlamp.
- Roomy seats, tilt steering wheel, radio, beverage holders and glove box with door.
- 2 in (5 cm) receiver hitch for hauling.



**FIND YOUR X**

	<b>XRT1550</b>		<b>XRT1550 SE</b>		<b>XRT1550 IntelliTrak</b>
	<b>4X4 GAS</b>	<b>4X4 DIESEL</b>	<b>4X4 GAS</b>	<b>4X4 DIESEL</b>	<b>4X4 DIESEL</b>
	This vehicle features exclusive IntelliTrak 4-wheel drive, either a 20.1 hp (15 kW) Kawasaki gas engine or a 20 hp (15 kW) Kubota diesel, 4-link semi-independent rear suspension, 4-wheel hydraulic disc brakes, a 4-point rollover protection system, seat belts, a standard bed capacity of 800 lb (363 kg), and 25 in (635 mm) mud or all-terrain tires.		This shift-on-the-fly 4-wheel drive vehicle offers the same engine options as the XRT1550 but features 4 forward-facing seats and an 800 lb (363 kg) capacity bed. It also offers semi-independent rear suspension, 4-wheel hydraulic disc brakes, a 4-point rollover protection system and seat belts. Chose 25 in (635 mm) mud or all-terrain tires.		Same standard features as the 4x4 diesel plus the industry's only fully hydraulic quick-changing tool attachment — one vehicle that does it all.
Engine	20.1 hp (15 kW) @ 3400 rpm per SAE J1349	20 hp (15 kW) @ 3600 rpm per SAE J1995	20.1 hp (15 kW) @ 3400 rpm per SAE J1349	20 hp (15 kW) @ 3600 rpm per SAE J1995	20 hp (15 kW) @ 3600 rpm per SAE J1995
4WD Engagement	Automatic, IntelliTrak		Automatic, IntelliTrak		Automatic, IntelliTrak
Electrical System	12-volt, 500 cca		12-volt, 500 cca		12-volt, 500 cca
Steering	Self-adjusting rack and pinion, Ackerman		Self-adjusting rack and pinion, Ackerman		Self-adjusting rack and pinion, Ackerman
Front Suspension	Independent double A-arms with coil-over shocks		Independent double A-arms with coil-over shocks		Independent double A-arms with coil-over shocks
Rear Suspension	4-link semi-independent, coil-over shocks		4-link semi-independent, coil-over shocks		4-link semi-independent, coil-over shocks
Brakes	4-wheel hydraulic disc		4-wheel hydraulic disc		4-wheel hydraulic disc
Chassis	Rustproof, non-corrosive box tube aluminum		Rustproof, non-corrosive box tube aluminum		Rustproof, non-corrosive box tube aluminum
Tires	Standard Mud (MT) 25 x 11 – 12 in (635 x 279 – 305 mm) Optional All-terrain (AT) 25 x 10.5 – 12 in (635 x 267 – 305 mm)		Standard MT 25 x 11 – 12 in (635 x 279 – 305 mm) Optional AT 25 x 10.5 – 12 in (635 x 267 – 305 mm)		Standard MT 25 x 11 – 12 in (635 x 279 – 305 mm) Optional AT 25 x 10.5 – 12 in (635 x 267 – 305 mm)
Instrumentation	Fuel/hour gauge, low oil warning light	Fuel/hour gauge, low oil and coolant high temperature warning lights	Fuel/hour gauge, low oil warning light	Fuel/hour gauge, low oil and coolant high temperature warning lights	Fuel/hour gauge, low oil and coolant high temperature warning lights
Overall L x W x H	122 x 59 x 82 in (310 x 149 x 209 cm)		154 x 59 x 80 in (391 x 149 x 204 cm)		With attachment arm: 136 x 58 x 79 in (345 x 147 x 200 cm)
Wheelbase	82 in (207 cm)		114 in (290 cm)		82 in (208 cm)
Ground Clearance Under Differential	8 in (21 cm)		8 in (21 cm)		7 in (19 cm)
Tire Tread	Front and Rear: 49 in (124 cm)		Front and Rear: 49 in (124 cm)		Front: 48 in (123 cm) Rear: 49 in (124 cm)
Weight	1450 lb (658 kg)	1597 lb (724 kg)	1630 lb (739 kg)	1734 lb (786 kg)	1800 lb (815 kg)
Forward Speed	25 mph (40 kph)		25 mph (40 kph)		25 mph (40 kph)
Load Bed Size	48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft <sup>3</sup>		48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft <sup>3</sup>		48 x 50 x 11 in (122 x 127 x 28 cm); 15 ft <sup>3</sup>
Maximum Payload	Standard: 800 lb (363 kg) Optional High capacity: 1050 lb (476 kg)		800 lb (363 kg)		800 lb (363 kg)
Vehicle Rated Capacity	Standard: 1200 lb (544 kg) Optional High capacity: 1450 lb (658 kg)		1600 lb (725.5 kg)		1200 lb (544 kg)
Standard Seating	Two		Four		Two
Fuel Tank	6.5 gal (25 L)		6.5 gal (25 L)		6.5 gal (25 L)